

# FTB-01



FTB-01 with Rubber Seal



FTB-01 with Cable Gland



## Termination Box FTB-01

### Feature

- Up to 12 drop cables
- Up to 12 Simplex SC adapters
- Can accommodate 1 x 8 ,1 x 4 PLC Splitter
- Maximum capacity is 24F
- 2 main ports is for 1 loop cable or 2 cables with max Ø 12 mm.
- The reserved port is for cables with max Ø 12mm
- The 12 small ports ,each port can hold 1 drop cable
- Bending radius > 30mm
- Outdoor use (IP 65)
- Designed for Wall and Pole mount applications
- Safety lock
- Rugged and durable construction for long term reliability (UV resistance)
- Design for small and medium volumes of fibre optic cables
- Reusable
- ROHS compliance

### Specification

Model No	FTB-01	FTB-01
Cable Port	2 rubber ports, each port for 1 cable with max Ø 12mm. 1 reserved port for 1 cable with max Ø 12mm.	2 cable gland, each port for 1 cable with max Ø 12mm. 1 reserved port for 1 cable with max Ø 12mm.
Can be used for uncut cable (loop cable)	Yes	No
IP Grade	IP 54	IP 65
Spliced fibre storage capacity	24F	
PLC splitter	1x4,1x8	
Adaptor Capacity	12 SC,12 LC duplex adaptor	
Drop Cable	12 drop cables with Ø 3mm or 3mmx2mm	
Application	Wall Mounting or Pole Mounting	
Dimensions	258mmx207mmx64mm (L x W x H)	

Unit 27 Fischer Park, 9 Blessing Ninela Rd, Hillcrest, Kwa-Zulu Natal, 3610

Company Reg: 2010/176961/23 (LeaderOptec)