

DJ-6HA-96 5P



DJ-6HA-96 5P Features

May be used for cut, uncut and taut sheath applications.

May be used for all fiber optic cable.

Sheath retention & central strength member termination system included.

Ribbed closure construction-lightweight plastic offers strength and resistance

to chemical and U.V attack

Installation and reentry with a minimum of tools

All hardware are captured

Closure can be flash tested

Protection class: IP68

ROHS compliance

Fiber Optic Splice Closure DJ-6HA

Application

Underground, Aerial, Vault, Pole Mounting and Wall Mounting

Specification

Model No	Splice Tray	Spliced fiber storage capacity(single fusion)	Size(mm) Height x diameter	Cable ports	Max. diameter of cable(mm)
DJ-6HA	DJ-6HA Capacity : 24 splices	96 splices (4 x24 splices)	540mm x 180 mm	1 oval port + 4 round ports	1 oval port for 1 cable with max 25 mm. 4 round ports , each port for 1 cable with max 19 mm
DJ-6HB	DJ-6HB Capacity : 24 splices	96 splices (4 x24 splices)	540mm x 180 mm	1 oval port + 4 round ports	1 oval port for 1 cable with max 25 mm. 4 round ports , each port for 1 cable with max 19 mm

Unit 27 Fischer Park, 9 Blessing Ninela Rd, Hillcrest, Kwa-Zulu Natal, 3610

Company Reg: 2010/176961/23 (LeaderOptec)